

CityLifter

Roller tarpaulin with lower swing wall

The certified CityLifter is perfectly suitable for city distribution and convinces by maximium payload, easy and fast opening and closing; an investment of lasting value, with decades of experience and convincing quality.



TOP ARGUMENTS

- Maximum payload: extremely leightweight construction with aluminium substructure results in minimum dead weight.
- Maximum time-saving: only one middle locker for fast opening and closing.











TOP QUALITY



substructure completely aluminium



smooth and simple opening mechanism



standard fittings: lateral pallet stop and smooth loading operation (inner front wall and corner posts on one level)

	CityLifter	SideLiner
body type	roller tarpaulin & swing wall	swing wall on the roof
certificates		
beverage certificate	✓	✓
draught beer certificate		✓
XL certificate	✓	✓
roll container certificate		✓
GS automotive industry Daimler certificate		
load dimensions (int.)		
lateral loading height (mm)	1.510 - 1.960 (in 50 mm steps)	2.000 - 2.600 (in 100 mm steps)
length (mm)	3.000 - 5.400 (customised)	4.600 - 13.600 (customised)
width (mm) between side walls (without pallet stop)	2.030 - 2.470	2.550
customised body length available	✓	✓
class of vehicle		
truck (t)	2.8 - 10	12 - 26
centre axle trailer (t)	3.5 / 10.5	10.5 / 18
turnable drawbar trailer (t)	3.5 / 10.5	10.5 / 18
semi-trailer (m)		(over 10 m with middle post)
swap body (mm)		