

SideLiner

Swing wall on the roof

The fully automatic superstructure can be opened at the push of a button. It is ready for loading/unloading within seconds and multifunctional in usage; an investment of lasting value, with decades of experience and convincing quality.



✓ Time-saving:

fast, automatic opening and closing within only 10 seconds. Automatic locking.

✓ Space-saving:

the lateral space needed for opening and closing the side-wall is about only 520 mm. additionally, low height chassis construction is possible.

✓ Weight-saving:

the application of leightweight panels increases the payload.







closed






TOP QUALITY

GEBOKIT







little lateral space needed



minimum roof overhang in opened condition

	CityLifter	SideLiner
body type	roller tarpaulin & swing wall	swing wall on the roof
certificates	,	
beverage certificate	✓	✓
draught beer certificate		✓
XL certificate	✓	✓
roll container certificate		✓
GS automotive industry Daimler certificate		
load dimensions (int.)		
lateral loading height (mm)	1.510 - 1.960 (in 50 mm steps)	2.000 - 2.600 (in 100 mm steps)
length (mm)	3.000 - 5.400 (customised)	4.600 - 13.600 (customised)
width (mm) between side walls (without pallet stop)	2.030 - 2.470	2.550
customised body length available	✓	✓
class of vehicle		
truck (t)	2.8 - 10	12 - 26
centre axle trailer (t)	3.5 / 10.5	10.5 / 18
urnable drawbar trailer (t)	3.5 / 10.5	10.5 / 18
semi-trailer (m)		(over 10 m with middle post)
swap body (mm)		,